

# Actuator MK7L

MK7L is an actuator equipped with brushless DC motor(BLDC) to output higher load as well as higher speed at max. load than ID10 series. A driver board is included, so the user can control the actuator to extend and retract simply by connecting a switch (dry contact). This actuator provides a thrust up to 10,000N at a speed of 25mm/sec, and its IP67, IP69K protection capability is suitable for use in harsh environments such as tractors, agricultural machines, lawn mowers, etc.



# **Features and Options**

- Main applications: Industry, Agriculture, Construction
- Motor type : 48V BLDC motor
- Max. rated load: 10,000N (Push/Pull)
- Max. static load: 13,600N
- Speed: 25mm/sec (Typical value)
- Spindle type: Ball screw
- Stroke: 203 (8") / 254 (10") / 305 (12") mm
- IP level: IP66 / IP67 / IP69K (Static; non-action)
- Salt spray test: 250 hours
- Preset limit switches
- Built-in brushless motor drive and electronic protection circuit board
- Extension tube material: Stainless steel
- Color: Black
- Power cord length: 500mm (with bare wires)
- Duty cycle: Max. 15% (60 sec. continuous operation in 400 sec. and is valid for operation within an ambient temperature of +5°C~+40°C)
- Operating ambient temperature: -25°C~+85°C (Full performance +5°C~+40°C)
- Storage ambient temperature: -40°C~+100°C
- Certified: CE Marking. EMC Directive 2014/30/EU.

## **Performance Data**



#### Remarks:

- (1) The typical speed is the instantaneous speed of the driver board output, rather than measuring the total start-stop travel distance divided directly by the total operating time.
- (2) The typical current means the average value neither upper limit nor lower limit, which measured under room temperature and stable power. The performance curves are made with typical values.

# **Drive Control Board Functions**

- The polarity of the actuator input power supply cannot be interchanged. The actuator's movement and direction are controlled by signals.
- Built-in soft start/stop functions, each about 0.6 seconds (not adjustable).
- The actuator completes stroke learning and memory before shipment. During use, it will decelerate before reaching the limit switch position to prevent impact.
- Over load protection: When the load reaches about 12,000N, the actuator will be stopped automatically.
- Voltage range protection: When the voltage is lower than 40V or higher than 68V, the actuator will be stopped automatically.
- Temperature protection: Temperature detection inside the driver board. When the temperature is detected higher than +85°C or below -40°C, actuator will be stopped automatically. It will resume operation until the high temperature is down to +80°C or the low temperature is raised to -35°C.
- Low temp. response: When the temperature inside the actuator is detected below 0°C, the overload protection setting value will be automatically increased by 30%, which will reduce the over current protection caused by low temperature.

# Dimensions

#### • Installation dimension = Retracted length (A) + Stroke (S)

Retracted length (A)501552	603

(Tolerance: ±5mm)

#### • Drawing





Unit: mm

#### • Front connector type





• Rear connector type

### • Pivot orientation of rear connector



# Cable with Flying Leads

#### • Wire definitions

	Wire color	Definition	Description
Power cable	Red	V+	Connect Red to positive. Connect Black to negative. Do not swap the polarity. Input voltage: 48V±10% Wire gauge: 12AWG
	Black	V-	
Signal cable	Blue	Actuator extends	Blue and white wires are shorted circuit: Actuator extends Yellow and white wires are shorted circuit: Actuator retracts Open circuit: Actuator stops Wire gauge: 18AWG
	Yellow	Actuator retracts	
	White	COM	

#### • Wiring



Remarks: Dashed lines are connected by the customer.

# Certifications

MK7L actuator is compliant with the following regulations, in terms of the essential conformity requirements of EMC Directive of 2014/30/EU.

Emission	Immunity
EN IEC 61000-6-3:2021	EN IEC 61000-6-1:2019
BS EN IEC 61000-6-3:2021	BS EN IEC 61000-6-1:2019

	MK7L- 48 - M5B - 30 - 254 - 0 0 0 0 L 9	1					
Input voltage	48: 48V DC						
Motor and spindle type	M5B: 12,000rpm / 5mm pitch / Ball screw						
Gear ratio	<b>30</b> : 30:1						
Stroke	<b>203</b> : 203mm (8") <b>254</b> : 254mm (10") <b>305</b> : 305mm (12")						
Front connector type	0: Standard						
Rear connector type	0: Standard						
<b>Pivot orientation of</b> <b>rear connector</b> (Refer to Page 3)	0: 0° (Standard) 3: 30° 6: 60° 9: 90° C: 120° F: 150°						
Reserved	0						
Limit switches	L: Limit switches						
IP level	9: IP66 / IP67 / IP69K						
Cable length	1: 500mm straight						



Terms of Use The user is responsible for the suitability of MOTECK products, and the products listed on the MOTECK website are subject to change without notice. MOTECK reserves the right to terminate sales or delete any products displayed on the website or listed in its catalog.

5